



*The 1997 Mustang Cobra has a powerful and refined DOHC V8 that produces 305 horsepower.*



**FORD SPECIAL VEHICLE TEAM/1997 MUSTANG COBRA**

**SVT™**

# FORD SVT MUSTANG COBRA TECHNICAL DATA



## ENGINE

Configuration	Longitudinally mounted, 90-degree V8, cast aluminum block and heads, iron cylinder liners, fully counterweighted forged crankshaft
Bore x Stroke	90.2mm x 90.0mm
Displacement	4,601cc/280cid
Compression ratio	9.85:1
Horsepower (SAE net)	305 hp @ 5,800 rpm
Torque	300 lb./ft. @ 4,800 rpm
Redline	6,800 rpm (fuel shut-off at 7,000 rpm)
Valvetrain	Double overhead cams (hollow camshafts), chain drive to exhaust cams, secondary chains from exhaust to intake cams, roller finger followers with hydraulic lash adjustment, ovate-wire beehive valve springs, four valves per cylinder
Intake valves	2 per cylinder, 37mm head diameter
Exhaust valves	2 per cylinder, 30mm head diameter
Fuel system	Sequential electronic fuel injection
Intake manifold	Tuned length thin-wall cast aluminum runners, cast aluminum plenum chamber
Throttle body	Twin 57mm bore throttle body, simultaneously opening
Air-mass sensor	80mm diameter
Port throttles	Electronically actuated 34mm port throttles open to secondary intake valves at 3,250 rpm
Exhaust manifolds	Cast high-silicon, molybdenum iron, manifold type, stud and nut attachment
Exhaust system	Dual, stainless steel, 2.25 in. diameter tubes

## DRIVETRAIN

Rear axle	8.8 in. limited-slip differential	
Driveshaft	Steel, with hardened yoke	
Transmission	Borg-Warner T45 5-speed manual; integral clutch housing	
Gear	Ratio	Speed
1st	3.37	45 mph (72 kph)
2nd	1.99	77 (124)
3rd	1.33	115 (185)
4th	1.00	152 (245)
5th	0.67	
Reverse	3.22	
Final drive	3.27	

## SUSPENSION

Front	Modified MacPherson strut, with separate spring on lower arm, 400/505 lbs./in. variable-rate coil springs, 29mm stabilizer bar
Rear	Rigid axle, upper and lower trailing arms, two leading hydraulic links, 165/265 lbs./in. variable-rate coil springs, shock absorbers, 27mm stabilizer bar

## STEERING

Type	Power assist, rack and pinion
Gear ratio	14.7:1 (on center)
Turns, lock to lock	2.38
Turning diameter	40.8 feet

## BRAKES

Front	13.0 in. (330mm) vented disc PBR twin-piston caliper
Rear	11.65 in. (296mm) vented disc, single-piston caliper
ABS	Bosch, three-channel, four-sensor system

## WHEELS AND TIRES

Wheels	Cast aluminum, diamond-cut surface, five-spoke, 17 x 8 in.
Tires	BFGoodrich Comp T/A ZR, 245/45ZR-17, unidirectional tread pattern

## COBRA INCLUDES

Supplemental restraint system: Driver- and passenger-side (air bag). Always wear your safety belt.

Tilt steering wheel

Anti-Lock Brake System

Articulated sport seats (four-way power for driver) with cloth/vinyl trim, cloth head restraint, and power lumbar support

Premium electronic AM/FM stereo cassette

Power Equipment Group: Dual electric remote control mirrors, power side windows, power door locks, power deck lid release

Rear window defroster

Air-conditioning/manual control

Speed control

Front floor mats

Dual illuminated visor mirrors

Remote keyless illuminated entry

Passive Anti-Theft System (PATS)

## AVAILABLE OPTIONS

Preferred Equipment Package, consisting of: Leather seating surfaces; Mach 460 electronic AM/FM stereo/cassette; Compact disc player; Total Anti-Theft System (TATS)

Rear deck spoiler

California emissions system

High-altitude principal use

## COLOR & TRIM

Exterior	Crystal White, Black Clearcoat, Rio Red Tinted Clearcoat, Pacific Green Clearcoat Metallic
Interior	Black Cloth, Saddle Cloth, Black Leather, Saddle Leather

## DIMENSIONS, CAPACITIES

Wheelbase	101.3 in./2,573mm
Length	182.5 in./4,636mm
Height	53.2 in. (53.3 in.)/1,351mm (1,354mm)
Width	71.8 in./1,824mm
Track, F/R	60.0 in., 58.7 in./1,524mm, 1,491mm
Head Room	38.2 in. (38.1 in.)/970mm (968mm)
Leg Room	41.9 in./1,064mm
Curb Weight	3,391 lbs. (3,531 lbs.)/1,541kg (1,605kg)
Fuel Tank	15.4 gal./58 liters
Weight Distribution, f/r, %	57/43

(Numbers in parentheses are for Convertible)

## PERFORMANCE

0-60 mph	5.9 seconds
Quarter mile	13.99 seconds @ 101.6 mph
Top speed	152 mph
Braking, 60-0 mph	127 ft.
Braking, 80-0 mph	227 ft.
80 ft. slalom	52.1 mph
100 ft. skidpad	0.89g

**Product Changes:** Following publication of this data, certain changes in standard equipment, options, prices and the like, or product delays, may have occurred which would not be included in these pages. Your Ford Dealer is your best source for up-to-date information. Ford Division reserves the right to change product specifications at any time without incurring obligations.

